

Star Vs the other Servo valve equivalent table

詳細はホームページ上のカタログを参照願います。・www.star-hydraulics.co.uk

Star Model	L/min Pv=70bar	特徴	ポート CPD(mm)	F特性	最高圧力 bar	MOOG	TSS	DOWTY	MICKERS	PEGASUS	REXROTH	ATCHLEY	ABEX
200	2,4,7	超小型	12.2	高		E050	401F	4633					
454	4,10,20	スリムBody	15.9	中、高		771,776	213F	4553、4653		121		208A、209	410
455	4,10,20,40	スリムBody	19.8	中、高		772	214F	4552、4655	SM4-10	132A		211A	415
456	60	スリムBody	23.8	中、高		773	215F	4657,4677	SM4-15	131,141	160A	218	
458	60	スリムBody	19.8	中					SH4				
460	4,10,20,40	CETOP3	ISO4401	中、高		D630、061					4WS2EM6		
500	4~60	Steel Body	22.2	中、高	500	760HP		4551		162M	4WS2Ex10A		
502	"	5 Port											
507	"	6 Port											
550	4~75		22.2	中、高		76、760	275F	4551	SH4-20	162M	4WS2Ex10A	215A	
552	"	5 Port(UK)	"					4592					
553	"	5 Port(USA)	"										
557	"	6 Port	"										
558	"	FR・Filter	"			J073	275F	4658					
550E	"	電気FB	"	高、超高速		765、769							
552E	"	5 Port	"										
590	20		"	超高速				4659					
592	20	5 Port(UK)	"	"				4689					
590-0	40,60	5 Port(USA)	"	"									
650	4~80	エコノミータイプ	22.2	中		62		4682、4683					
652	"	5 Port	"	"									
750	95,125	スリムBody	34.9	中			(216F)	4684				225	425
890	95,150,230	DIN10372	50.8	中、高	280(500)	72	504F	4550		1282A		261	450
892	"	5 Port	"										
897	"	6 Port	"										
1550	4~60	CETOP5	DIN24340	中、高		631	304F				4WS2Ex10A		
1552	"	5 Port	"	"		"	"						
1554	4~70	5 Port Diff.	"	"		"	"						
1650	"	エコノミータイプ	"	中		"	"						
60	230	3段型、P弁550-HI	50.8	高		E079-1		4660					
130	490	3段型、P弁590VH	57,2x79.2	高		79-2		4660					
160H	600	As130	"	"		79-2							
200H	750	As130	"	"		79-2							
240H	900	As130	"	"		79-2							

*Starサーボ弁カタログのダウンロード手順:homeページ→Products→ご希望サーボ弁の写真上で左クリック→PDFカタログがダウンロードできます。